

DATA SHEET

RESIN VINYL FLAKE

Coloured Vinyl Flake

DESCRIPTION			BENEFITS	
Coloured, 6mm vinyl flakes designed for use in all types of decorative flake flooring systems. The flakes are randomly shaped and come in a range of 8 popular colour combinations.			 Water-based technology. Optimal flexibility and strength. UV-stable. Compatible with all major resin types. 	
USES				
Common uses for Resin Vinyl Flake include decorative			COVERAGE	
flake flooring systems in:			As per application requirements. Typically $2m^2/kg$ for full	
• Garages	• Homes	• Patios	As per application requirements. Typically 2m²/kg for full coverage, and 5-40m²/kg for partial coverage.	
	Retail Outlets	Cafes/Restaurants	The theoretical yield for full coverage is:	
• Kitchens	Aged Care Facilities	• Offices	10kg bucket @ 2m²/kg = 20m²	
• Schools	• Toilets & Changerooms	• Walkways		
PRODUCT DETAILSType:6mm (1/4") vinyl flake.Colour:8 colour combinations - see colour chart.Pack Size:10kg buckets.				

RESIN VINYL FLAKE

PRODUCT NOTES

- Do not apply flakes in the rain.
- Flakes are random in shape due to manufacturing process.
- While the sizing is consistent, a small amount of fines will be present in each bucket.
- While flakes are UV stable, the overall UV performance will be determined by the coating system used.
- Test prior to use if unsure of resin compatibility.

APPLICATION

Broadcast the flake immediately after basecoat application. Wear spiked shoes to walk around on the freshly laid epoxy without leaving prints.

Can be applied by hand or pneumatic/electric/petrol hopper-blower gun.

STORAGE

Store flakes in sealed, original buckets at room temperature and in a dry environment to avoid moisturerelated product degradation. Seek advice from your local council regarding accepted disposal methods.

FIRST AID

CAUTION: KEEP OUT OF REACH OF CHILDREN.

IF ON SKIN: Rinse skin after manually handling and wash contaminated clothing before re-use. IF IN EYES: Rinse cautiously with water for several minutes. IF INHALED: Remove person to fresh air. IF exposed, concerned, unwell or irritation persists: Get medical advice/attention.



Ph: 1300 EPOXIES www.realworldepoxies.com

WARRANTY DISCLAIMER: The technical data given herein has been compiled for your help and guidance and is based upon our experience and knowledge. However as we have no control over the use to which this information is put, no warranty express or implied is intended or given. We assume no responsibility whatsoever for coverage, performance or damages, including injuries resulting from use of this information or of products recommended herein. Date of Issue - May 21.