

FIX IN FIVE

Fast-cure Patching Compound

DESCRIPTION

A solvent-free, high-viscosity epoxy designed for rapid repair of cracks, divots and hollows in the subfloor.

Quality materials are selected to create a high-strength patching resin that is ready to sand or coat in 5-minutes.

Fix in Five can be used in combination with RWE Ezypatch and Filler to modify viscosity and make it easier to grind.

USES

Common uses for Fix in Five include subfloor patching in:

- Garages
- Homes
- Patios
- Car Parks
- Retail Outlets
- Cafes/Restaurants
- Kitchens
- Aged Care Facilities
- Offices
- Schools
- Toilets
- Walkways

PRODUCT DETAILS

Type: Two-pack epoxy (100% solids).
 Colour: Clear.
 Finish: Gloss.
 Mix Ratio: 1:1 v:v.
 Pack Size: 500mL.

BENEFITS

- ✓ Cures hard in 5 minutes.
- ✓ Easy 1:1 by volume mix.
- ✓ Nozzled containers for more control and cleaner use.
- ✓ Superior adhesion and strength compared to bogs.
- ✓ Can be used with stir-in fillers to adjust viscosity.
- ✓ Tintable formulation for less visible repairs.
- ✓ Not a Dangerous Good for quicker, easier shipping.

PROPERTIES

Hardness ASTM D-2280	85-90 Shore D
--------------------------------	---------------



FIX IN FIVE

CURING TIMES

	Time (@ 25°C)
Pot Life	- 4 minutes
Set (touch)	- 5 minutes
Set (hard)	- 30 minutes
Full Cure	- 1 hour

- Approximate time frames for full kit @ 25°C.
- Curing times will decrease with increasing temperature (+10°C will halve curing times, -10°C will double them).

PRODUCT NOTES

- Hardened resin can be sanded in 5 minutes, however can be slightly gummy and a little difficult to grind. Adding fillers to the resin can result in a "drier" patch that is easier to grind.
- Part B has a strong odour that may be disruptive to some sensitive environments.
- Do not attempt to alter cure time by changing mix ratio.
- Clean up with MEK, acetone or methylated spirits.

SURFACE PREPARATION

Surfaces should be structurally sound and free of contamination, laitance and any loose material.

Ensure surface is clean, dry and dust-free again if there's a delay before application.

MIXING

For full safety instructions, consult SDS. Wear protective clothing, goggles and gloves to prevent skin and eye contact.

Mix product at a ratio of 1:1 by volume. Only work with small volumes (500mL or less) to avoid product hardening before use.

Squeeze required amount of Part A and Part B into a suitable container and mix with a stiff spatula until a consistent colour is obtained. Scrape sides to ensure all product is taken in. Add fillers and/or pigment as required.

APPLICATION

Pour mixed product into repair site and smooth using a suitable trowel or spatula. Repairs can be tidied via sanding 5 minutes after application.

STORAGE

Keep containers closed when not in use. Store below 40°C. Do not store in direct sunlight. Shelf life is at least 12 months in original, unopened container. Seek advice from your local council regarding accepted disposal methods.

FIRST AID

CAUTION: KEEP OUT OF REACH OF CHILDREN.

IF ON SKIN: Remove immediately all contaminated clothing. Rinse skin with water. **IF IN EYES:** Rinse cautiously with water for several minutes. Immediately call a POISON CENTRE (Australia - 13 11 26) or doctor/physician. If skin irritation occurs: Get medical advice/attention.



Ph: 1300 EPOXIES www.realworldepoxies.com

WARRANTY DISCLAIMER: The technical data given herein has been compiled for your help and guidance and is based upon our experience and knowledge. However as we have no control over the use to which this information is put, no warranty express or implied is intended or given. We assume no responsibility whatsoever for coverage, performance or damages, including injuries resulting from use of this information or of products recommended herein.
Date of Issue - February 23.